

STS410

Technical specifications

	STS410-8	STS410-8 HA
Video Input	8 participants and PowerPoint in a Quicklink Studio Conference room & NDI inputs	8 participants and PowerPoint in a Quicklink Studio Conference room & NDI inputs
Conference calling	Support for simultaneous video conferencing call inputs including Microsoft Teams, Zoom, Discord and Slack	Support for simultaneous video conferencing call inputs including Microsoft Teams, Zoom, Discord and Slack
Skype TX integration	Native support for up to 4 Skype callers	Native support for up to 4 Skype callers
Network Video Input	NDI/RTMP/UDP/SRT	NDI/RTMP/UDP/SRT
SDI Video Input/Output	8 configurable inputs/outputs. E.g. 2 inputs, 6 outputs	8 configurable inputs/outputs. E.g. 2 inputs, 6 outputs
Video Output	SDI (DIN1.0/2.3)	SDI (DIN1.0/2.3)
Network Video Output	8 independent contributor outputs via NDI. Program as NDI/RTMPSRT. Preview as NDI/RTMP/SRT.	8 independent contributor outputs via NDI. Program as NDI/RTMPSRT. Preview as NDI/RTMP/SRT.
Stream Output	3 x resolution independent streaming outputs. Independently configurable with simultaneous recording	3 x resolution independent streaming outputs. Independently configurable with simultaneous recording
Multiviewer Output	4 x multiviewer outputs supporting standard display resolutions using any combination of available connections. 1x HDMI. 3x DisplayPort	4 x multiviewer outputs supporting standard display resolutions using any combination of available connections. 1x HDMI. 3x DisplayPort
Media Sources	Image (png, jpg, jpeg, gif, fra, bmp) & Media Source (mp4, ts, mov, flv, mkv, avi, mp3, ogg, aac, wav, gif, webm)	Image (png, jpg, jpeg, gif, fra, bmp) & Media Source (mp4, ts, mov, flv, mkv, avi, mp3, ogg, aac, wav, gif, webm)
Third-party overlays	Integration with Singular and Flowics	Integration with Singular and Flowics
Keyers	Chroma Key filter	Chroma Key filter

Subject to change without notice

STS410

Technical specifications

	STS410-8	STS410-8 HA
Macros	Record, store, edit and automate commands and user-configured operation sequences	Record, store, edit and automate commands and user-configured operation sequences
Recording	Recording of program output (mp4, mov, mkv, ts, m3ub) and independent for each contributor (mov)	Recording of program output (mp4, mov, mkv, ts, m3ub) and independent for each contributor (mov)
Storage	2TB internal Supports shared storage integration	2 x 2TB internal Supports shared storage integration
Screen Capture	Still images from external locations	Still images from external locations
Support for hardware controllers through hotkeys (shortcuts)	✓	✓
Audio	4 channels 4 XLR in, 4 XLR out	4 channels 4 XLR in, 4 XLR out
Local Audio Input	Balanced XLR (line) 3.5mm stereo jack	Balanced XLR (line) 3.5mm stereo jack
Network Audio	NDI/Dante/Livewire+ AES67	NDI/Dante/Livewire+ AES67
Tally	Software-based tally return and overlay text	Software-based tally return and overlay text
Genlock	Genlock input supporting SD (Bi-level) or HD (Tri-level) reference signals	Genlock input supporting SD (Bi-level) or HD (Tri-level) reference signals
NIC	1 x 10 Gigabit NIC 1 x 2.5 Gigabit NIC 1 x 1 Gigabit NIC	1 x 10 Gigabit NIC 1 x 2.5 Gigabit NIC 1 x 1 Gigabit NIC
High Availability 2 x 2TB Solid State Drives in RAID configuration. Hot swappable dual power supply for redundancy		Included
System Physical	4U chassis	4U chassis

Subject to change without notice



Contact: Quicklink, Bay Studios, Fabian Way, Swansea, SA1 8QB, United Kingdom
Tel: +44 1792 720880 - www.quicklink.tv - sales@quicklink.tv

STS410

Rear Diagram

