

STS410

Technical specifications

	STS410-8	STS410-8 HA
Video Input	8 participants and PowerPoint in a Quicklink Studio Conference room & NDI inputs	8 participants and PowerPoint in a Quicklink Studio Conference room & NDI inputs
Conference calling	Support for simultaneous video conferencing call inputs including Microsoft Teams, Zoom, Discord and Slack	Support for simultaneous video conferencing call inputs including Microsoft Teams, Zoom, Discord and Slack
Skype TX integration	Native support for up to 4 Skype callers	Native support for up to 4 Skype callers
Network Video Input	NDI/RTMP/UDP/SRT	NDI/RTMP/UDP/SRT
SDI Video Input/Output	8 configurable inputs/outputs. E.g. 2 inputs, 6 outputs	8 configurable inputs/outputs. E.g. 2 inputs, 6 outputs
Video Output	SDI (DIN1.0/2.3)	SDI (DIN1.0/2.3)
Network Video Output	8 independent contributor outputs via NDI. Program as NDI/RTMPSRT. Preview as NDI/RTMP/SRT.	8 independent contributor outputs via NDI. Program as NDI/RTMPSRT. Preview as NDI/RTMP/SRT.
Stream Output	3 x resolution independent streaming outputs. Independently configurable with simultaneous recording	3 x resolution independent streaming outputs. Independently configurable with simultaneous recording
Multiviewer Output	4 x multiviewer outputs supporting standard display resolutions using any combination of available connections. 1x HDMI. 3x DisplayPort	4 x multiviewer outputs supporting standard display resolutions using any combination of available connections. 1x HDMI. 3x DisplayPort
Media Sources	Image (png, jpg, jpeg, gif, fra, bmp) & Media Source (mp4, ts, mov, flv, mkv, avi, mp3, ogg, aac, wav, gif, webm)	Image (png, jpg, jpeg, gif, fra, bmp) & Media Source (mp4, ts, mov, flv, mkv, avi, mp3, ogg, aac, wav, gif, webm)
Third-party overlays	Integration with Dizplai, Flowics, HYPER and Singular	Integration with Dizplai, Flowics, HYPER and Singular
Keyers	Chroma Key filter	Chroma Key filter

Subject to change without notice

STS410

Technical specifications

	STS410-8	STS410-8 HA
Macros	Record, store, edit and automate commands and user-configured operation sequences	Record, store, edit and automate commands and user-configured operation sequences
Recording	Recording of program output (mp4, mov, mkv, ts, m3ub) and independent for each contributor (mov)	Recording of program output (mp4, mov, mkv, ts, m3ub) and independent for each contributor (mov)
Storage	2TB internal Supports shared storage integration	RAID Configuration, Hot Swappable Drive Bay 2 x 2TB internal Supports shared storage integration
Support for hardware controllers through hotkeys (shortcuts)	✓	✓
Audio	8 channels 8 XLR in, 8 XLR out	8 channels 8 XLR in, 8 XLR out
Local Audio Input	Balanced XLR (line) 3.5mm stereo jack	Balanced XLR (line) 3.5mm stereo jack
Network Audio	NDI/Dante/Livewire+ AES67	NDI/Dante/Livewire+ AES67
Genlock	Genlock input supporting SD (Bi-level) or HD (Tri-level) reference signals	Genlock input supporting SD (Bi-level) or HD (Tri-level) reference signals
NIC	1 x 10 Gigabit NIC 1 x 1 Gigabit NIC	1 x 10 Gigabit NIC 1 x 1 Gigabit NIC
Power	Single Power Supply	Dual Redundant Power Supply
High Availability 2 x 2TB Solid State Drives in RAID configuration. Hot swappable dual power supply for redundancy		Included
System Physical	4U chassis	4U chassis

Subject to change without notice

STS410

Rear Diagram

